



### LED Strip lighting

LED Ultra thin Flexible strip from Lumenstar is bright, efficient and reliable. It offers excellent color quality, high CRI and is fully dimmable. cULus Approved.

3 Year Warranty



JOB#

LED Flex Tape	LED / M	Voltage	Light Output / Ft.	Watt / M	Ordering Increment †	LED Type	Cut Length	Dimensions in mm	Colour Temp	CRI
Indoor - with 3M sticky tape on the back										
LS-FLI-IA*-12-60-3K** LS-FLI-IB*-12-60-3K** LS-FLI-ID*-12-60-3K**	60	12V DC	145	4.8	3M (10 ft.) 5M (16.4 ft.) 25M (82 ft.)	3528	50mm	W8 x H1.5	2700K, 3000k 4100k, 5500k Red, Green, Blue	>90
LS-FLI-ID-24-3K	60	24V DC	145	4.8	25M (82 ft.)	3528	50mm	W8 x H1.5	3000k	>90
LS-FLI-IB*-12-120-3K** LS-FLI-ID*-12-120-3K**	120	12V DC	290	9.6	5M (16.4 ft.) 25M (82 ft.)	3528	25mm	W8 x H1.5	3000k, 5500k	>90
LS-FLI-3B-12-48-3K**	48	12V DC	360	11.5	5M (16.4 ft.)	5050	50mm	W10 x H1.5	3000k, 5500k	>85
LS-FLI-1B-24-120-3K**	120	24V DC	475	14.4	5M (16.4 ft.)	2835	25mm	W6.5 x H1.5	3000k, 5500k	>90
LS-FLI-2B-12-72-CRV-3K**	72	12V DC	260	7.2	5M (16.4 ft.)	2835	50mm	W10 x H1.5	3000k, 5500k	>90
LS-FLI-1B-12-120-CCT	120	12V DC	360	9.6	5M (16.4 ft.)	3528	50mm	W8 x H1.5	2600k to 6500k	>90
LS-FLI-4B-24-224-DTW	224	24V DC	494	18	5M (16.4 ft.)	2016	62mm	W12 x H1.5	3000k dims to 2000k	>90
Moisture Proof - with silicone coating, and 3M sticky tape on the back										
LS-FLM-3B-12-48-3K**	48	12V DC	360	11.5	5M (16.4 ft.)	5050	50mm	W10 x H1.5	3000k, 5500k	>85
LS-FLM-2B-24-120-3K**	120	24V DC	475	14.4	5M (16.4 ft.)	2835	50mm	W8 x H1.5	3000k, 5500k	>90
Waterproof - Jacketed. Includes clips and waterproof connector on both ends										
LS-FLO-1A*-12-60-3K** LS-FLO-1B*-12-60-3K**	60	12V DC	145	4.8	3M (10 ft.) 5M (16.4 ft.)	3528	50mm	W10 x H1.5	3000k, 5500k	>90

\*Use the following code for desired length when applicable:

A =3M (10 ft.)	B =5M (16.4 ft.)	C =10M (32.8 ft.)	D =25M (82 ft.)	† E =Custom
----------------	------------------	-------------------	-----------------	-------------

\*\*When ordering, use designated code for color temperature:

27K =2700K	3K =3000K	41K =4100K	55K =5500K	R =Red	G =Green	B =Blue
------------	-----------	------------	------------	--------	----------	---------

† Custom lengths available. Contact us with your request.



